

ActivGrip Advance KEV

OIL GRIP PERFORMANCE WITH CUT RESISTANCE



DESCRIPTION

ActivGrip Advance KEV combines Kevlar® fiber with Towa's MicroFinish® technology, delivering outstanding cut resistance and excellent grip performance. The 13-gauge, seamless Kevlar® liner and "open back styling" keeps hands cool while delivering excellent flexibility to minimize hand fatigue and thereby increase productivity. Towa is well-known for the performance of its product ActivGrip Advance, and the soft yet durable Nitrile MicroFinish® coating of ActivGrip Advance KEV means that the gloves can be used on virtually any dry or slippery surface.

FEATURE

- Cut resistance**
ActivGrip Advance KEV together with Kevlar, a choice for bullet resistant vest, offers the high assurance of cut resistant protection.
- Oil Resistant**
Unlike similar gloves available in the market, ActivGrip Advance KEV offers more promising protection to oil penetration. Double coated surface keeps hands clean for oily handling.
- Confidence**
With MicroFinish® technology, the Advance KEV promises its performance under dry, wet and oily conditions.
- Comfort**
A 13-gauge seamless liner and ergonomic design assure a maximum comfort and minimum hand fatigue.

TECHNOLOGY








Available with Kevlar®, ActivGrip Advance KEV assures the performance under oily condition.

APPLICATIONS

- Automotive
- Assembly
- Machine Operation
- Oily Material Handling



PRODUCT

| | | | |
|------------------|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Material | Nitril | | |
| Size | 7/S - 11/XXL | | |
| Liner | 13-Gauge Seamless Kevlar® | | |
| Length | - | | |
| Color | Yellow & Black | | |
| Size & Hem Color |  7/S |  8/M |  9/L |
| |  10/XL |  11/XXL | |

TECHNICAL

EN388

| | | | | | | |
|----------|---|---|---|---|---|---|
| Abrasion | 0 | 1 | 2 | 3 | 4 | |
| Cut | 0 | 1 | 2 | 3 | 4 | 5 |
| Tear | 0 | 1 | 2 | 3 | 4 | |
| Puncture | 0 | 1 | 2 | 3 | 4 | |



4342

Kevlar® is a registered trademark of E. I. du Pont de Nemours and Company.