102[™] MID PEAK - SLIP RATCHET - VENTILATED

THE EVO2[™] OFFERS THE MOST ECONOMICAL TOP LEVEL PROTECTION

TECHNICAL SPECIFICATION

HEAD PROTECTION

SHELL: High Density

Polyethylene (HDPE)

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

CHAMLON[™] SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested



SLIP RATCHET: One Touch[™] Slip Ratchet version of the EVO2^m is so simple to fit that it can be adjusted with just one finger

Touch





CONFORMITY

Conforms to EN397

EN 50365 for Helmets for use in low voltage installations
EC Certificate Number 0279, issued by BSi Product Certification
Low dome profile
Incorporates a rain channel
Compatible with other JSP safety products

- Available in a choice of colours
- Company personalisation available by printing

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature



MANUFACTURING FOR SAFETY WWW.JSP.CO.UK

TEL: +44 (0)1993 826050



MID PEAK - SLIP RATCHET - VENTILATED

THE EVO2[™] OFFERS THE MOST ECONOMICAL TOP LEVEL PROTECTION

TECHNICAL SPECIFICATION

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10 Weight: 3.8kg (Approx)





	ONS (

Size:	530 - 640mm
Weigh	t: 350g (Approx)

HELMET COLOURS



WWW.JSP.CO.UK

MANUFACTURING FOR SAFETY UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050

EN EN397 Yes STANDARD EN50365 Yes Impact Resistance Yes 50 Joules PERFORMANCE **Electrical Insulation** EN50365 1000V TEMPERATURE -30°C Yes RESISTANCE SHELL HDPE Yes MATERIAL Recyclable Yes HARNESS HDPE Yes MATERIAL Textile Yes **OPTIONS** Universal Accesories Yes Reflective CR2 option Yes Ventilated Yes Integrated Eyewear Yes HARNESS SYSTEM JSP 3D Yes Slip Ratchet **OPTIONS** Yes 6 pts Yes CHINSTRAP 4 pts Yes 10G0 Front Yes **OPTIONS** Rear Yes Side Yes MOQ Logo

LIMITATIONS OF USE

HELMET FEATURES

Protection will only be offered if the helmet is fitted correctly Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer The harness, when in contact with the skin may cause

Individual Name

Yes

allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer

 (\square)

