V03™ **MID PEAK - SLIP RATCHET - VENTILATED**

EVO3™ IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2 & MK3 HELMETS

TECHNICAL SPECIFICATION

HEAD PROTECTION

SHELL: **High Density**

Polyethylene (HDPE)

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

WEBBING HARNESS: HDPE Strap & Webbing Clips with Polyester Webbing Straps



CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature



Mk3 evolution

CONFORMITY

Touch

SLIP RATCHET: One Touch[™] Slip Ratchet version of the EVO3[™] is so simple to fit that it can be adjusted with just one finger

Conforms to EN397, N50365 & ANSIZ89

- EN 50365 for Helmets for use in low voltage installations
- EC Certificate Number 0279, issued by BSi Product Certification Meets the retro reflective performance requirements of EN12899 when fitted with CR2 Reflective kit
- Meets optional Molten Metal Splash performance
- Wide size range. Slip or wheel ratchet High comfort fit
- Available vented or unvented. Available with mid or micro peak
- Company personalisation available by printing



MANUFACTURING FOR SAFETY WWW.JSP.CO.UK

TEL: +44 (0)1993 826050

ТМ **MID PEAK - SLIP RATCHET - VENTILATED**

EVO3™ IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2 & MK3 HELMETS

TECHNICAL SPECIFICATION

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity:	10
Weight:	3.8kg (Approx)



DIMENSIONS OF HELMET

Size:	530 - 640mm		
Weight: 375g (Approx)			

HELMET COLOURS



WWW.JSP.CO.UK

MANUFACTURING FOR SAFETY

UKSALES@JSP.CO.UK

TEL: +44 (0)1993 826050



HELMET FEATURES

EN STANDARD	EN397 EN50365	Yes Yes
PERFORMANCE	Impact Resistance Electrical Insulation	Yes 50 Joules EN50365 1000V
TEMPERATURE RESISTANCE	-30°C	Yes
SHELL MATERIAL	HDPE Recyclable	Yes Yes
HARNESS MATERIAL	HDPE Textile	Yes Yes
OPTIONS	Universal Accesories Reflective CR2 option Ventilated Integrated Eyewear	Yes Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Slip Ratchet 6 pts	Yes Yes Yes
CHINSTRAP	4 pts	Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice The attention of users is also drawn to the dangers of

modifying or removing any of the original component parts, other than as recommended by the manufacturer

 (\mathbf{n})

