



Introducing the new  
**HY-SPEC® 25**

# PERFECT FOR INTERIOR & EXTERIOR PERIMETER SEALING OF WINDOWS AND DOORS

HY-SPEC® 25 is a highly elastic hybrid sealant for use where movement occurs, especially between dissimilar materials such as; uPVC, aluminium, composite and timber frames sealed into masonry, brick or plaster walls.

**Hodgson**  
SEALANTS



## Low modulus

Highly elastic, low modulus sealant tested to ISO 11600 25 LM and conforms to CE Mark EN15651-1:F-EXT-INT-CC: CLASS 25LM. Specifically designed for where movement occurs, especially between dissimilar materials such as perimeter sealing of uPVC frames and meets the requirements of BS 8213-4 for the installation of windows and doors.

## Paintability

HY-SPEC® 25 can be over-painted with water-based paints and wood stains.

Available in:

- ☐ WHITE
- ☐ BLACK
- ☐ GREY
- ☐ ANTHRACITE GREY
- ☐ BROWN

## Suitable for interior and exterior use

Weather and UV resistant, will not shrink or crack. Excellent adhesion to most materials, even in damp conditions.

## Excellent tooling & application properties

Properties described by multiple time served NVQ skilled sealant applicator professionals were “very positive indeed” the sealant is “excellent to gun out with good tooling properties”.

## USES

Sealing of construction joints; equally suited to sealing of many internal and external joints in the building envelope / façade and connection joints where a paintable elastic sealant may be required.

