

MAXIMUM SECURITY hardened steel bolt, zinc plated wih anti-rattle sleeve.

18mm bolt stroke. 7mm zinc plated steel rod with 40mm thread length, easily adapted for non standard door installations. Two lengths available 305mm (12 inch)

& 152mm (6 inch). "Centre Punch" tip to mark centre of

keep.

Die cast zinc alloy body mechanism. Fixing holes tapped M5. Fixings included.

Deep finger recess and large lever for ease in operation. Corners 2.5mm radius for easy maching

of cut out.

▲ FINISHES AVAILABLE Mill finish - for customers own finish. Silver - Satin chrome. Bronze - Powder coat.

PRODUCT CODES				
LENGTH	FINISH	FLAT	RADIUS	
305mm	MILL	62.00F12	62.00R12	
(12 inch)	SILVER	62.01F12	62.01R12	
	BRONZE	62.02F12	62.02R12	
SHIPPING WEIGHT 2.52Kg. PER 10				

LENGTH	FINISH	FLAT	RADIUS	
152mm	MILL	62.00F06	62.00R06	
(6 inch)	SILVER	62.01F06	62.01R06	
	BRONZE	62.02F06	62.02R06	
SHIPPING WEIGHT 2.05Kg. PER 10				

Bolt guide by door manufacturer.

▲ FLOOR SOCKET KEEP Sprung loaded, dust resistant, satin chrome finish.

PRODUCT	SOCKET KEEP	
CODE	62.035	
SHIPPING WEIGHT 2.1Kg. PER 30		

GUARANTEE

AXIM FLUSH BOLTS ARE GUARANTEED FOR 30 MONTHS FROM THE DATE OF MANUFACTURE AGAINST DEFECT IN MATERIAL AND WORKMANSHIP. THIS GURANTEE IS VOID IF THE PRODUCT HAS BEEN INCORRECTLY INSTALLED OR DAMAGED IM USE. CLAIMS FOR DAMAGE INCURRED OR WORK DONE THEREON WILL NOT BE ACCEPTED.

AXIM RESERVE THE RIGHT TO UPDATE ITS PRODUCT SPECIFICATIONS WITHOUT PRIOR NOTICE.









R 50_

146

129

RADIUSED

FACE









20.5

26.5

for

40



FLAT FACE