


# 470

## SANDBLAST RESIST TAPE

VentureTape® 470 is a strong, conformable 4 mil vinyl sandblasting tape coated with a specially formulated removable acrylic pressure sensitive adhesive (PSA). Specifically designed to be blade cut by hand or plotter, VentureTape 470 withstands light sandblasting and removes cleanly with no adhesive transfer or residue and is ideal for use as a sandblast stencil for glass, wood, and other materials as well as for use as a paint mask.

### Product Construction



### Features & Benefits

- Strong, conformable material applies easily and removes cleanly after sandblasting or painting operations
- Vinyl material cuts well and the thin material allows for sharp sandblasting profiles
- Performs well over a wide range of environmental conditions
- Resistant to moisture, acids, alkalis, oils, and other chemicals
- In stock product available for immediate delivery

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness <sup>a</sup>	4.6 mils	0.12 mm	PSTC-133
Peel Adhesion <sup>a</sup>	14 oz/in	3.9 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	12 lb/in	54.2 N/25 mm	PSTC-131
Elongation	100 %	100 %	PSTC-131
Service Temperature	-40 to 225 °F	-40 to 107 °C	

<sup>a</sup> - excluding liner

<sup>a</sup> - 20 minute dwell

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.